





Certification # \_\_\_\_\_ Name of Bowling Centre \_\_\_\_\_ Date \_\_\_\_\_, 20\_\_\_\_ Page \_\_\_\_\_

INSTRUCTIONS: CHECK FOR CROSSWISE TILT AND DEPRESSIONS AT EACH TEST POINT INDICATED. COMPLETE ALL BOXES  
 SPECIFICATION: MAXIMUM .040 (40/1000)

ITEM	DISTANCE FROM FOUL LINE	REMEMBER TO COMPLETE TILTS & DEPRESSIONS	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	
*22	Measure Between 10-15'	Crosswise Tilts >																
		Depressions	- 6" to 12" from 10 pin side >															
			- Middle of Bowling Lane >															
	Insert Distance	- 6" to 12" from 7 pin side >																
*22	Measure Between 30-40"	Crosswise Tilts >																
		Depressions	- 9" to 15" from 10 pin side >															
			- Middle of Bowling Lane >															
	Insert Distance	- 9" to 15" from 7 pin side >																
*22	Measure Between 50-55'	Crosswise Tilts >																
		Depressions	- 12" to 18" from 10 pin side >															
	Insert Distance		- 12" to 18" from 7 pin side >															

REMARKS: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_